

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 August 2004 (19.08.2004)

PCT

(10) International Publication Number
WO 2004/069107 A1

(51) International Patent Classification⁷: **A61F 2/46**, 2/34

(21) International Application Number:
PCT/GB2004/000405

(22) International Filing Date: 3 February 2004 (03.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0302409.8 3 February 2003 (03.02.2003) GB

(71) Applicant (for all designated States except US): **DEPUY INTERNATIONAL LIMITED** [GB/GB]; St Anthony's Road, Beeston, Leeds LS11 8DT (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FENTON, Gary**


[GB/GB]; 66-68 Broomfield Road, Fixby, Huddersfield HD2 2HG (GB). **ALFONSI, Stefano** [IT/GB]; Flat 2, 4 West Grove Road, Harrogate HG1 2AD (GB). **MOORE, Gary** [GB/GB]; 74 Aire Road, Wetherby LS22 7UE (GB). **FLETT, Magnus** [GB/GB]; 27 Hatfield View, Wakefield WF1 3SN (GB).

(74) Agent: **BELCHER, Simon, James**; Urquhart-Dykes & Lord LLP, Tower House, Merrion Way, Leeds LS2 8PA (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: AN INSTRUMENT FOR POSITIONING A CUP COMPONENT OF AN ORTHOPAEDIC JOINT PROSTHESIS



(57) Abstract: An instrument (30) for positioning a cup component (2) of an orthopaedic joint prosthesis comprises a shaft (32), and a flange (34) towards the end (35) of the shaft on which the cup component can be fixed. The flange (34) extends from the shaft (32) transversely, and can be retracted from an in-use position in which the flange (34) can be received in a groove (6) in the internal surface of the cup component, when positioned over the said end of the instrument, to a retracted position in which the flange (34) is withdrawn towards the axis of the shaft (32) from the in-use position. Retraction of the flange (34) allows the cup component to be released from the instrument (30). The flange (34) comprises a plurality of radially spaced apart flange portions (36). At least one of the flange portions (36) is retractable and biased towards the in-use position.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*